



RON MAN

5 1/2" Fascia Gutter



New upright, tension brake, aluminum spool and coil scale



Polyurethane Drive Train

- Eliminates the need to load coil prior to transportation (less material waste)
- Eliminates slippage from cold weather and condensation
- Rollforms all standard metals with minimal or no adjustment

Electrical and Control System

- Push button entry and exit end controls with safety wiring and "jog" feature
- 3/4 HP, 110 volt, single phase motor, 13.6 ampere

Structural Steel Frame

- Welded tubular frame

Modular Turnstile Upright System

**2 Year Warranty
On Parts**

KWM[®]
Gutterman^{INC.}



5 1/2" Fascia Gutter

Power

3/4 HP, 110 volt, single phase,
13.6 ampere, totally enclosed
fan cooled (T.E.F.C.) motor

Dimensions

Length – 132 1/2" (336.55 cm)
Height – 48" (122.0 cm)
Width – 24" (61.0 cm)

Weight

Approximately 1,300 lbs. (589.7 kg)

Drive

Powered polyurethane drive rollers
via chains and sprockets

Shear

Front pull guillotine

Speed

Approximately 35 feet per minute

Controls

Push button entry and exit end controls
with "jog" feature

Recommended Materials

14" and 15" wide

Material	Maximum Gauge
Aluminum	.032
Copper	16 oz.– 20 oz. 3/4 hard
Painted Steel	24

Options

- Machine mount cradles
- Fixed upright system
- Additional runout support stands
- CE Certified wiring
- Additional turnstiles
- Additional spools
- Flange assembly for roofing



Quick release turnstile and transfer bars

