

BG7[™] 7" Commercial Box Gutter Machine


U.S. PATENT NO. 5,394,722 U.S. PATENT NO. 5,740,687 Profiles Standard

Factory Installed Options


Solving Industrial Gutter Demands By Having Features and Options That Custom Fit Your Needs.

STANDARD FEATURES:

- New and Improved Polyurethane Drive Rollers
- Quick Change Power Pac™, Gas or Electric
- Computer Length & Batch Control
- Hydraulic Drive and Shear
- Power Interruption Safety Circuit
- Gutter Recognition Safety Photo Eye
- Length Control Limit Switch
- Push Button RUN/JOG Controls at Entry and Exit Ends
- Welded Tubular Steel Frame
- Dual Overhead Decoiler Rack
- One Expandable Arbor



Inside Flang



OPTIONS

TR12 12,000 lb. (5,500 kg) Capacity

NATM Compliant Tandem Axle Trailer, with Crane Lifting Eyes, Four-Drop

Foot Stabilizing Jacks and Elec. Brakes with Breakaway Kit

Decoiler Reel 16" (400mm) ID DR01-16 Decoiler Reel 20" (500mm) ID DR01-20 Expandable Arbor (16" to 20" ID) **EXA**

(400mm to 500mm)

ROS-10 Ten Ft. (3m) Sections of Variable

Height Run Out Table

QCPP-E Quick Change Power Pac™- Electric

• 7.5 Hp, 220VAC, 60 Hz, 3Ph,

18 Amps

• 5 Hp, 220VAC, 50 or 60 Hz, 1Ph,

30 Amps

QCPP-G Quick Change Power Pac[™]- Gas

16 Hp Electric Start Engine

PROFILES - FACTORY INSTALLED OPTIONS

BF4 4" Back Flange (100mm) HK7 Alcoa hook Assembly IF7 1" Inside Flange (25mm)

SPECIFICATIONS

BG7 GUTTER MACHINE

Length 14' 6" (4.4m) Width 4' (1.7m)

Height 4'3" (1.3m) w/ Over Head Rack

2'8" (.8m) w/o Over Head Rack

Weight 1800 lbs. (820kg)

BG7 ON TRAILER

Length 17'6" (5.3m) Width 7' (2.1m)

Height 6'3" (1.9m) with reel Weight 3400 lbs. (1550kg)

SPEED

60 ft/min (18m/min) Approx.

DRIVE

Hydraulically Driven Polyurethane Rollers

Hydraulically Powered, Hardened Tool Steel Blades and Dies, Gutter

Recognition Safety Photo Eye

COIL WIDTH

20" (500mm) Straight Back, HK7, IF7

24" (600mm) BF4

MATERIALS FORMED

Steel 26 ga. to 22 ga. (.4mm to .8mm) (painted, galvanized, aluminized)

Aluminum .032" to .050" (.8mm to 1.3mm) Copper

20 oz. to 24 oz. 3/4 hard

(.7mm to .8 mm)

WARRANTY

- Limited three year parts / one year labor
- · Limited lifetime separation on drive rollers
- · Limited lifetime on stainless steel forming rollers



Run Out Table



Quick Change Power Pac™



Electronic Controller