


IRON MAN

7" Seamless Rollformer

Also available in 6-7" combo



Use the touch screen to automatically control product length, add for miters, if applicable, and keep a total of daily material ran and total footage. Password protected.

Polyurethane Drive Train

- Eliminates the need to load coil prior to transportation (less material waste)
- Rollform 24 gauge steel
- Eliminates slippage from cold weather and condensation

.002 Hard Chrome Plated Steel Forming Rollers

- Rollforms all recommended materials with minimal or no adjustment
- Free-floating forming rollers produce less pressure and allow for more product uniformity

Electrical and Control System

- Push button entry and exit end controls with safety wiring and "jog" feature
- 11/2 HP, 110 volt, single phase motor, 18 ampere

Structural Steel Frame

- Welded tubular frame

Modular Turnstile Upright System & Transfer Bars

- Transfer bars (ease of coil loading)

ROCK SOLID GUARANTEE:

3-YEARS Parts & Labor/Mechanical

• 1-YEAR Parts & Labor/Electrical

www.GutterSupply.com

935 Campus Dr., Mundelein, IL 60060 ■ E-mail sales@guttersupply.com

Phone (847) 283-0006 ■ Toll-free (888) 909-RAIN





IRON MAN

7" Seamless Rollformer

SPECIFICATIONS

Power 11/2 HP, 110 volt, single phase, 18 ampere, totally enclosed fan cooled (T.E.F.C.) motor	Dimensions Length – 168" (378.46 cm) Height – 48" (127.0 cm) Width – 24" (61.0 cm)													
Weight Approximately 1,490 lbs. (675.85 kg)	Drive Powered polyurethane drive rollers via chains and sprockets													
Shear Front pull guillotine	Speed Approximately 35 feet per minute													
Controls Push button entry and exit end controls with "jog" feature	Options <ul style="list-style-type: none"> • Smart Machine (automated length control) • Machine mount cradles • Additional runout support stands • CE Certified wiring • Additional turnstiles • Additional spools • Alcoa style hook • Roof flange 1" • Trailer riser pad 													
Recommended Materials Maximum width 18" <table> <thead> <tr> <th>Material</th><th>Maximum gauge</th></tr> </thead> <tbody> <tr> <td>Painted steel</td><td>24</td></tr> <tr> <td>Galvalume</td><td>24</td></tr> <tr> <td>Aluminized steel</td><td>24</td></tr> <tr> <td>Ternecoat steel</td><td>24</td></tr> <tr> <td>Aluminum</td><td>.032</td></tr> <tr> <td>Copper</td><td>16 oz.–20 oz. 3 /4 hard</td></tr> </tbody> </table>		Material	Maximum gauge	Painted steel	24	Galvalume	24	Aluminized steel	24	Ternecoat steel	24	Aluminum	.032	Copper
Material	Maximum gauge													
Painted steel	24													
Galvalume	24													
Aluminized steel	24													
Ternecoat steel	24													
Aluminum	.032													
Copper	16 oz.–20 oz. 3 /4 hard													

www.GutterSupply.com

935 Campus Dr., Mundelein, IL 60060 ■ E-mail sales@guttersupply.com

Phone (847) 283-0006 ■ Toll-free (888) 909-RAIN

