

Innovation. Quality. Versatility.

The World's Finest Portable Rollforming Equipment



SSH[™] Roof Panel Machine

www.GutterSupply.com 1-888-909-RAIN Info@GutterSupply.com

The World's Finest Portable Rollforming Equipment

SSH™ MultiPro

Light Commercial / Residential Multi-Profile Roof Panel Machine

- The high performance solution to your residential and light commercial needs.
- Seven available panel profiles in variable widths, multiple gauges and various material types



STANDARD FEATURES		
Polyurethane Drive Rollers	Powder-Coated Frame & Covers	
Power Interruption Safety Circuit	Runs Up to 24 Gauge Steel	
Hydraulic Drive & Shear	Length Control Limit Switch	
Included: PLC Batch / Length Computerized Controller	Welded Tubular Steel Frame	
Choice of: Quick-Change™ Profile Roller System	Push Button RUN/JOG Controls	
Choice of: Quick-Change™ Power-Pack (Gas or Electric)	UL Rated Panels (Must Be Certified by UL for Recognition)	
Choice of: One Pair of Bead, Pencil, Striation or V-Rib Rollers	Industry's Best Warranty	


SPECIFICATIONS		
SH PANEL MACHINE		
ength	12' 10" (3.9m)	
Vidth	5' (1.5m)	
leight	4' 3" (1.3m) with Over Head Rack 2' 0" (.6m) without Over Head Rack	
Veight	3,725 lbs. (1,700kg)	
SH ON TRAILER		
ength	17′ 6″ (5.3m)	
Vidth	7' (2.1m)	
leight	6' 3" (1.9m) with Reel	
Veight	5,275 lbs. (2,400kg)	
OIL WIDTHS		
4" to 24" (355mm to 610mm)		
MAXIMUM COIL DIAMETER		
2" (812mm) with the Overhead Reel Rack		
5" (1,143mm) with the Free Standing Decoiler		
INISHED PANEL WIDTHS		
0" to 20" (254mm to 508mm) - Note: Variable Depen	nding on Panel Profile	
MATERIALS FORMED		
ainted Steel	30 ga. to 24 ga. (.3mm to .6mm) (painted, galvanized, aluminized)	
ainted Aluminum	.027" to .040" (.7mm to 1.0mm)	
Copper	16 oz. to 20 oz. 3/4 Hard (.5mm to .7mm)	
HEAR		
lydraulically Powered, Infinitely Adjustable, Hardened	Tool Steel Blades & Shear Dies	
anel Recognition Safety System		
PRIVE		
lydraulically Driven via Chain, Sprocket & Gear		
PEED		
0 ft./min (18.3m/min) Approx.		

The World's Finest Portable Rollforming Equipment

SSH™ Panel Profiles (Choice of)



These field formed panels have demonstrated compliance with UL580, Class 90 when a UL certificate accompanies the machine producing panel.



PROFILES	
SSH100 * †	1" high x 1/2" wide (25.4mm x 12.7mm) mechanically seamed panel. Includes a hand seamer and clip relief.
SSH150 * †	1-1/2" high x 1/2" wide (38.1mm x 12.7mm) mechanically seamed panel. Includes a hand seamer and clip relief.
SSH450 * / 450SL *	1-1/2" high x 1/4" wide (38.1mm x 6.4mm) snap clip panel / snap lock panel. Includes clip relief rollers.
FFH100	1 " snap seam (25.4mm) with slotted fastener flange for clipless installation. Includes clip relief rollers and automatic "no chip" rotary slotter.
FFH150	1-1/2" snap seam (38.1 mm) with slotted fastener flange for clipless installation. Includes clip relief rollers and automatic "no chip" rotary slotter.
T-Panel	1/2" to 1-1/2" high (12.7mm to 38.1mm)

- * Can make T-Panel † Suitable for Zinc
- All roller systems include shear dies and clip relief rollers.
- SSH100, SSH150 and SSH450/450SL Roller Systems all use identical left side roller sets.
- FFH100 and FFH150 also share identical left side roller sets.

If you purchase or own one of these roller systems, you can add any of the other right side systems at a reduced price!

- Warranty: Three years parts (including electrical) / Three years labor
 - Limited lifetime separation on drive rollers
 - Limited lifetime on stainless steel forming rollers

U.S. PATENT NO. 6,772,616

Rib Roller Options











CLIP RELIEF

BEAD RIBS (STANDARD OR WIDE)

PENCIL RIBS (SMALL OR LARGE)

V-RIBS (SMALL OR LARGE)

STRIATION RIBS

Innovation. Quality. Versatility.

The World's Finest Portable Rollforming Equipment

The NTM Roof Panel Machine Family:







Check Out the SSH Online:





www.GutterSupply.com 1-888-909-RAIN Info@GutterSupply.com Proud Members of:





